



DONGGUAN HAIXIANG ADHESIVE PRODUCTS CO., LTD

Factory address: The Industrial Zone of Bajiao wo su wu in Wanjiang area, Dong guan City, Guangdong Province, China

TEL: +86 769-39022795 FAX: +86 769-89280809

Website: www.haixiangtape.en.alibaba.com

HX-6005 美纹纸胶带物理性能标准表

(HX-6005 Masking tape physical performance standard sheet)

序号 (No.)	项目 (Item)		单位 (Unit)	检测标准 (Test Standard)	检验方法 (Test way)	测试数据 (Technical Data)
1	外观 (appearance)		\	胶粘带呈卷状，表面平整，色泽均匀，两侧平齐无折痕，溢胶色斑显著变形等缺陷。(our tape is per roll, tidy surface, uniform colour, two sides is tidy, not fold, and stain and so on defect.	目测 (visual test)	\
2	解卷剥离 (stripping)		\	不允许有胶粘剂脱落或迁移至下层离型纸背面 (Don't allow glue to drop or move to the reverse side of release paper)	GB-4850-1984	\
3	厚度 (Thickness)		um	150 ± 5	\	150
4	涂胶宽度 (Glue width)		mm	≥ 1020	\	1020
5	密度 (density)		g/m ²	100 ± 5	\	104
6	初粘 (Initial tack)	内	钢球号 (#)(Ball No.)	≥ 18	GB-4852-1984	18
		外				
7	持粘性 (Permanent adhesion)	内	H/25mm	≥ 4.0	GB-4851-1998	7.5
		外				
8	抗拉强度 (Tensile strength)		N/25mm	80 ± 5	GB-2792-1988	80
9	伸长 (Elongation)		9-13%			
10	抗温 (Temp resistance)		80°C			
11	测试条件 (Test condition)		温度 23 ± 2° C 相对温度 65 ± 5° C Temperature 23 ± 2° C relative temperature 65 ± 5° C			